



D Schneidring · PSR Progressiv Stop Ring

für EO 24° Anschluss



Schneidring:
D



Progressiv Stop Ring:
PSR

Reihe	D1	Schneidring D Bestellzeichen							Progressiv Stop Ring PSR Bestellzeichen			Gewicht g/1 St.
		L1	Stahl, verzinkt Cr(VI) frei	PN (bar)	Edelstahl	PN (bar)	Messing	PN (bar)	L2	Stahl, verzinkt Cr(VI) frei	PN (bar)	
LL	04	6,0	D04LLX	100	D04LL71X	100	D04LLMSX	63	—	—	—	0,3
	06	7,0	D06LLX	100	D06LL71X	100	D06LLMSX	63	—	—	—	0,8
	08	7,0	D08LLX	100	D08LL71X	100	D08LLMSX	63	—	—	—	1,0
	10	7,0	D10LLX	100	D10LL71X	100	D10LLMSX	63	—	—	—	1,3
	12	7,5	D12LLX	100	D12LL71X	100	D12LLMSX	63	—	—	—	1,6
	15	7,5	D15LLX	100	D15LL71X	100	D15LLMSX	63	—	—	—	1,6
L	06	9,5	—	—	—	—	D06LMSX	200	9,5	PSR06LX	500	1,7
	08	9,0	—	—	—	—	D08LMSX	200	9,5	PSR08LX	500	2,2
	10	10,0	—	—	—	—	D10LMSX	200	10,0	PSR10LX	500	3,1
	12	10,0	—	—	—	—	D12LMSX	200	10,0	PSR12LX	400	3,5
	15	10,0	—	—	—	—	D15LMSX	200	10,0	PSR15LX	400	4,5
	18	10,0	—	—	—	—	D18LMSX	200	10,0	PSR18LX	400	5,5
	22	10,5	—	—	—	—	D22LMSX	100	10,5	PSR22LX	250	7,3
	28	10,5	—	—	—	—	D28LMSX	100	10,5	PSR28LX	250	9,4
	35	13,0	—	—	—	—	D35LMSX	100	13,0	PSR35LX	250	20,0
	42	13,5	—	—	—	—	D42LMSX	100	13,0	PSR42LX	250	23,0
	16	10,5	—	—	—	—	D16SMSX	250	10,0	PSR16SX	630	5,6
	20	12,5	—	—	—	—	D20SMSX	250	13,0	PSR20SX	420	11,4
S	06	9,5	—	—	—	—	D06LMSX	400	9,5	PSR06LX	800	1,7
	08	9,0	—	—	—	—	D08LMSX	400	9,5	PSR08LX	800	3,2
	10	10,0	—	—	—	—	D10LMSX	400	10,0	PSR10LX	800	3,1
	12	10,0	—	—	—	—	D12LMSX	400	10,0	PSR12LX	630	3,5
	14	10,0	—	—	—	—	D14SMSX	400	10,0	PSR14SX	630	3,9
	16	10,5	—	—	—	—	D16SMSX	250	10,0	PSR16SX	630	5,6
	20	12,5	—	—	—	—	D20SMSX	250	13,0	PSR20SX	420	11,4
	25	12,5	—	—	—	—	D25SMSX	250	13,0	PSR25SX	420	13,3
	30	13,0	—	—	—	—	D30SMSX	250	13,0	PSR30SX	420	19,3
	38	13,5	—	—	—	—	D38SMSX	200	13,0	PSR38SX	420	22,5

$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$