


FM EO2-Funktionsmutter

für Stahl-Rohr



X1) Haltering

Bau- reihe	D1 	T1	L1	S1	Bestellzeichen				Gewicht g/1 St.
					FM...CF Stahl verzinkt Cr(VI) frei passiv. + Versiegelung Dichtung		FM...VITCF Stahl verzinkt Cr(VI) frei passiv. + Versiegelung Dichtung		
					NBR	PN (bar)	FKM	PN (bar)	
LL	04 06	M 08x1,0 M 10x1,0	11,0 11,5	10 12	FM04LLCF —	100 —	— —	100 —	5 6
L	06	M 12x1,5	14,5	14	FM06LCF	500	FM06LVITCF	500	12
	08	M 14x1,5	14,5	17	FM08LCF	500	FM08LVITCF	500	17
	10	M 16x1,5	15,5	19	FM10LCF	500	FM10LVITCF	500	22
	12	M 18x1,5	15,5	22	FM12LCF	400	FM12LVITCF	400	30
	15	M 22x1,5	17,0	27	FM15LCF	400	FM15LVITCF	400	48
	18	M 26x1,5	18,0	32	FM18LCF	400	FM18LVITCF	400	70
	22	M 30x2,0	20,0	36	FM22LCF	250	FM22LVITCF	250	94
	28	M 36x2,0	21,0	41	FM28LCF	250	FM28LVITCF	250	106
	35	M 45x2,0	24,0	50	FM35LCF	250	FM35LVITCF	250	160
	42	M 52x2,0	24,0	60	FM42LCF	250	FM42LVITCF	250	244
S	06	M 14x1,5	16,5	17	FM06SCF	800	FM06SVITCF	800	20
	08	M 16x1,5	16,5	19	FM08SCF	800	FM08SVITCF	800	23
	10	M 18x1,5	17,5	22	FM10SCF	800	FM10SVITCF	800	37
	12	M 20x1,5	17,5	24	FM12SCF	630	FM12SVITCF	630	39
	14	M 22x1,5	20,5	27	FM14SCF	630	FM14SVITCF	630	60
	16	M 24x1,5	20,5	30	FM16SCF	630	FM16SVITCF	630	72
	20	M 30x2,0	24,0	36	FM20SCF	420	FM20SVITCF	420	121
	25	M 36x2,0	27,0	46	FM25SCF	420	FM25SVITCF	420	221
	30	M 42x2,0	29,0	50	FM30SCF	420	FM30SVITCF	420	248
	38	M 52x2,0	32,5	60	FM38SCF	420	FM38SVITCF	420	367

$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$